

Umrechnungstabelle/Conversion Table

Anschlussbezeichnung/Connection type

	SAE	Anschluß mm	Connection inch.	Gewinde/Thread
Bördel/Flare	1/4"	6	1/4"	7/16-20 UNF
	5/16"	8	5/16"	5/8"-18 UNF
	3/8"	10	3/8"	5/8"-18 UNF
	1/2"	12	1/2"	3/4"-16 UNF
	5/8"	16	5/8"	7/8"-14 UNF
	3/4"	18	3/4"	1-1/16"-14 UNF
	7/8"	22	7/8"	1-1/4"-12 UNF

		Anschluß mm	Connection inch.	
Löt/Braze		(6,35) 6	1/4"	
		(9,5) 10	3/8"	
		(12,7) 12	1/2"	
		16	5/8"	grau unterlegte: mm/inch ~ identisch
		22	7/8"	
		(28,6) 28	1-1/8"	
		35	1-3/8"	greyed cells: mm/inch ~ identical
		(41,3) 42	1-5/8"	
		54	2-1/8"	
		(66,7) 64	2-5/8"	
		(79,4) 76	3-1/8"	
		89		
		(104,8) 108	4-1/8"	

Leistung/Capacity

1 TR (tons of refrigeration)	3,52 kW
1 kW/h	3600 kJ
1 PS	0,735 kW
1 kcal/h	1,163 W

Länge/Length

1 inch (Zoll, ")	25,4 mm
1 ft	30,48 cm

Druck/Pressure

1 psi	0,07 bar
1 bar	14,5 psi
1 bar	0,1 MPa
1 kPa	0,01 bar
100 kPa	1 bar
1 Mpa	10 bar

Temperatur/Temperature

°C	(°F-32)/1,8
°F	(°C*1,8)+32